METHOD AND APPARATUS FOR HYDRAULIC FRACTURING ANALYSIS AND DESIGN

*****

Anthony P. Peirce

Eduard Siebrits

BACKGROUND OF THE INVENTION

Field of the Invention

This invention relates to an apparatus and method used to design, monitor and evaluate petroleum reservoir fracturing. The invention employs a method to estimate, from available data, the shape of a fracture by way of a numerical simulator which replicates the physical behavior of the hydraulic fracturing process. The size and features of a fracture may be controlled to maximize well productivity following fracturing of the well.

Description of the Prior Art

In hydraulic fracturing, thousands of gallons of fluid are forced under high pressure underground to split open the rock in a subterranean formation. Proppant or propping agent is carried into the fracture by the viscosified fluid, and deposited into the fracture. Proppant provides a permeable flow channel for formation fluids such as oil and gas to travel to the wellbore and above the ground surface.

Fracturing involves many variables, including: viscosity of the fracturing fluid, rate of leak-off of fracturing fluid into the reservoir, proppant carrying capacity of the fluid, viscosity of the fluid as a function

5   of temperature, time history of fluid volumes (i.e. the amount of fluid pumped over a given period of time), time history of proppant volumes, fluid physical constants, proppant properties, and the geological properties of various zones in the reservoir.

10   Currently, fracturing design is accomplished using PC-based programs such as, for example, Schlumberger's FracCADE simulator (FracCADE is a trademark of Schlumberger Technology Corporation). Some of the currently available software has the ability to use what is known in the

15   industry as "pseudo" three dimensional (P3D) hydraulic fracture simulators. Pseudo (P3D) methods are capable of estimating height growth for single fracture geometry's, but cannot accurately represent fracture geometry in more complex treatments that involve multiple geological layers

20   underground (known as "laminated" reservoirs).

Other software has the ability to use what is known in the industry as planar three dimensional ("PL3D") hydraulic

fracture simulators. Methods employing PL3D accurately take into account geologic layers. One such program, known commercially as GOHFER (GOHFER is believed to be a trademark of Stim-Lab and the Marathon Oil Company), provides grid

5 oriented hydraulic fracture replication capabilities. This grid oriented program, and its mode of operation, is seen in Figure 7. As the front of the fracture moves forward, calculations are made in which each individual grid is either "on" or "off" depending upon whether or not more than

10 half of the individual grid is "covered" by the advancing fracture as it moves outward from the wellbore. If more than one-half of the grid element is covered, then the element is estimated to be fully active. The disadvantage of this system of estimating fracture growth is that it

15 produces too much numerical noise at the fracture tip, and hence in the output data.

Other PL3D methods of simulating fractures include the TerraFrac three dimensional fracturing simulator (TerraFrac is a trademark of the TerraTek Company). This simulator

20 operates as seen in Figure 8, using estimates that are based upon a method of a moving mesh. This method shows less noise than the GOHFER method, because it uses triangle

shaped elements which form a tighter fit with the advancing

fracture front. However, it recalculates the entire mesh

element set again and again, using large amounts of

computing power.

5   What is needed in the industry is a software

implemented method that is capable of accurately and

efficiently estimating a fracturing event -- before the

event, during the event, or after the event. A method and

process is needed that is capable of properly accounting for

10   all kinds of layer contrasts, including elastic properties,

layer toughness, leakoff parameters, and confining stress.

A method is needed which can estimate pinch point scenarios,

estimate runaway height growth, and join or separate

fractures in the same plane. A process is needed that does

15   not require periodic "re-meshing", as typically is required

with many prior art moving mesh techniques. A technique in

which only the fracture front is tracked is highly

desirable. Further, a system which is not limited to only

an "on/off" binary system for elements would be beneficial.

20   A system that facilitates rapid updates of the solution at

each step is needed.

SUMMARY OF THE INVENTION

A petroleum reservoir PL3D hydraulic fracturing

modeling apparatus and method is disclosed that incorporates

5   a complete hydraulic fracturing analysis system for the

design, monitoring, or evaluation of a petroleum reservoir.

The invention uses industry accepted techniques of analysis.

A computer generated estimate showing fracture growth in

physical dimensions is presented.   This evaluation is used

10 to determine the dimensions and shape of the hydraulic

fracture that may be formed under a given set of parameters

and conditions.

The method includes a rigorous hydraulic fracturing

estimation method for a geologically laminated petroleum

15 reservoir.   The method uses industry accepted hydraulic

fracturing analysis techniques. Techniques accepted in the

industry include: (1) material balance of hydraulically

pumped fluids and proppant, (2) energy balance of the

fracture tip with the surrounding reservoir host rock, and

20 (3) equilibrium of the stresses and strains in the layered

petroleum reservoir due to forced introduction of the

hydraulic fracture into the reservoir.

A method and device is disclosed in which the device comprises a means for storing instructions, said instructions adapted to be executed by a processor of a computer. Further, the instructions when executed by the

5 processor should be capable of executing a process comprising the steps of obtaining a first data set, the first data set comprising at least one of the following: time history of fluid volumes, time history of proppant volumes, fluid properties, proppant properties, and

10 geological properties. Additionally, the method includes a means for providing the first data set to a computer, the computer having a processor capable of executing instructions, the computer further having electronic storage means with stored equations comprising hydraulic fracturing

15 relationships. A further step relates to computing by said processor a first set of values by manipulating said first data set using said stored equations. It is possible then to determine from said first set of values dimensions of a hydraulic fracture, the dimensions including fracture height

20 and length, fracture width, and fluid pressures as a function of time. In a further embodiment, the step of converting said first set of values into a set of output

data is performed, the output data representing fracture

dimensions and fluid pressures as a function of pumping

time.   Further, one may then display the output data on a

computer monitor, transmit the data by satellite or remote

5   link to another location for further processing or review,

or even include a feedback control loop to control the

fracturing event in real time.

In one embodiment, a step of determining from said

first set of values the dimensions of a hydraulic fracture

10   using a mesh of elements is performed.   In that step, the

dimensions, including fracture height and length, fracture

width and fluid pressures as a function of time, are

ascertained.   Further, the invention may deploy elements

which are capable of being only partially active, further

15   wherein the recalculation of fully active elements is not

required during determination of the first set of values.

The invention more accurately and efficiently estimates

fracture growth and orientation.

20   **BRIEF DESCRIPTION OF THE DRAWINGS**

Figure 1 shows the actual physical data that is

provided by way of a first data set into a computer;

8

Figure 2 shows a first data set and a CD-ROM or other

magnetic media upon which is written instructions that can

be read by the computer in executing the method of the

invention;

5   Figure 3 depicts the data that is provided to the

system bus of the microprocessor;

Figure 4 shows a laminated geological reservoir divided

into zones or layers, and the fracture boundary and fluid

boundaries at a particular time;

10   Figure 5 is a flowchart of the fracture growth process;

Figure 6 is a continuation of the flowchart shown in

Figure 5;

Figure 7 reveals the method of calculation using a

prior art "on/off" mesh method;

15   Figure 8 depicts a prior art method of calculating

fracture growth requiring recalculation of triangular

element mesh parameters at each time step;

Figure 9 shows a method of this invention which is

capable of recognizing and using partially active elements

20   to estimate the growth and propagation of a fracture;

Figure 10 is a close-up or expanded view of grid

element 47 from Figure 9;

Figure 11 is an expanded view of grid element 54 of Figure 9;

Figure 12 shows a typical cross-section through a laminated reservoir containing multiple hydraulic fractures which the model in this invention can simulate;

Figure 13 shows a single fracture from Figure 12, broken into square elements for simulation purposes;

Figure 14 shows active and inactive elements for the current fracture;

Figure 15 reveals typical layer interfaces and the coordinate system used later in this document;

Figure 16 shows a typical numerical mesh with layers and their interfaces;

Figure 17 is a flow diagram;

Figure 18 is a sample FracCADE zone input screen showing how an operator can select the zones which apply to the wellbore under consideration;

Figure 19 shows a FracCADE fluids input screen; and

Figure 20 reveals a typical display of a fracture profile with proppant dissemination confining stresses, and fracture width along the wellbore shown.

DETAILED DESCRIPTION

A petroleum reservoir hydraulic fracturing modeling

5 apparatus and method is disclosed which incorporates a

complete hydraulic fracturing analysis system for the

design, monitoring, or evaluation of petroleum reservoir

hydraulic fracturing performance, using industry accepted

techniques of analysis. A computer generated estimation

10 method is used to determine the dimensions and shape of the

hydraulic fracture in a computerized methodology with

maximum efficiency. A primary goal is to maximize well

performance and production.

The method includes a rigorous hydraulic fracturing

15 model for a geologically laminated petroleum reservoir, and

it uses industry accepted hydraulic fracturing analysis

techniques. Techniques accepted in the industry include:

(1) material balance of hydraulically pumped fluids and

proppant, (2) energy balance of the fracture tip with the

20 surrounding reservoir host rock, and (3) equilibrium of the

stresses and strains in the layered petroleum reservoir due

to forced introduction of the hydraulic fracture into the

reservoir.

11

Turning now to Figure **1**, a pumping schedule, the reservoir layer confining stresses and properties, a perforated interval and depth, wellbore data, and fluid and proppant properties are provided in a first data set to a

5   computer. In Figure **2**, one can see the input of the first data set representing the physical properties necessary to determine size and growth of the fracture. That data is provided to the computer, and combined with the software instructions (shown here as CD-ROM based) to facilitate the

10   calculation of values representing physical dimensions of the fracture and pressures inside the fracture. Also shown is an output format to a printer.

     Figure **3** shows how time history and other pertinent data is provided to the system bus of the computer and

15   thereby made available for coordination with the processor, recorder, and software.

     In Figure **4**, a reservoir **23** is shown. Pumping truck **24** provides fluid at high pressures and flow rates to wellhead **25**, which is operably connected to the wellbore **27**

20   at or near the ground surface **26**. The Figure shows the fracture boundary **30** at a particular time. Two fracture fluid boundaries **28** and **29** also are indicated in the Figure.

The fluid boundaries reveal separate types or compositions

of pumped fluid.

Various zones or laminations of underground geological

forms can be seen.   In Figure **4**, the fracture preferably is

5   stopped prior to the water bearing zone seen at the lower

portion of Figure **4**.

Figures **5** and **6** show a flowchart of software

implemented steps of this invention wherein input data is

provided to generate layer interface locations.   Next,

10 layer properties are assigned, followed by assignment of

maximum expected fracture height and length.   Then, a

numerical "parent" mesh is generated.   An elastic influence

coefficient matrix is generated next, followed by the

assignment of the current time step.   The steps are

15 followed as set forth in Figure **6**, and then a check step for

global mass balance is performed.   If no mass balance is

achieved, then the loop is repeated until convergence of the

solution is obtained.   After updating the new fracture

layout, the time is checked, and if it has reached a user-

20 defined limit, the simulation is terminated and the output

data is sent to storage.

Figure **7** shows binary mesh method **35** of the prior art employing a regular mesh with wellbore **31**. The active elements of the mesh are shown. Fully active element **34** and inactive element **32** can be seen in the Figure. The

5 methodology followed in this prior art example is that if the leading edge **33** covers more than 50% of the element, then the element is considered to be fully active, and if less than 50%, it is considered to be inactive. Thus, it is a binary system of approximating the function.

10 Figure **8** shows another prior art methodology in which triangular elements are used to closely match the fracture front. Wellbore **38** issues a fracture having triangular element **39** and fracture leading edge **40**. In this methodology, a closer "fit" is formed between the elements

15 and the fracture leading edge, thereby forming somewhat improved approximation over the prior art method of Figure **7**. However, prior art methods employing the method of Figure 8 require recalculation, or "re-meshing", after a number of time steps. Such recalculation requires

20 interpolation and very large amounts of computing power and time, which is a significant disadvantage of this method.

In Figure **9**, the partial element methodology of this invention is shown. Partial element methodology **41** shows a wellbore **42** from which a fracture grows. An inactive element **43** is seen, and a fully active element **44** also is

5   shown. Notably, literature reference 14 below describes an example of partial elements as applied in the mining industry to model tabular excavations. The partial element methodology of this invention is different, however, and is applied in a completely different context. For example, the

10 current invention applies to fracture growth from a wellbore, not to excavations in the mining industry. There are many considerations that apply to mining that do not apply to fracturing. Further, another difference between this invention and the procedure disclosed in reference 14

15 is that the reference applies to fixed shapes, not to moving boundaries, as in the invention of this application.

Partially active elements **45** and **46** show how an element may be considered only partially active or activated in this invention. Figure **10** shows a close up of partially active

20 element **47** having fracture leading edge **48** with crossing points **49** and **50**, respectively. Straight line **51** is erected between the crossing points, and it forms the boundary for

15

the active portion of the element **53** and the inactive

portion of the element **52**. Figure 11 likewise shows many of

the same features for element 54 of Figure **9**.

Figures **12-20** are to be described in detail in the

5   further detailed description set forth below.

The computer components shown here are those which may

be purchased and which are commercially available in the

industry.   Minimum PC requirements are a 200 MHz processor,

comprising about 16 MB RAM, and 100 MB of hard drive space.

10   Most commercially available personal computers meeting these

specifications will be sufficient to practice the invention.

A computer programmer of skill in the art, upon

reviewing this specification and drawings, could construct a

program to carry out the steps of the method.   Once such

15   instructions are placed on magnetic media and made available

to the processor of a computer having the specifications set

forth above, the method of the invention will be executable.

The data input may be by hand, from logs, via communication

ports or channels, or by any other means which serves to

20   provide actual data for the steps of the inventive method.

Data may comprise surface pumping measurements, output from

monitoring equipment, surface microprocessor or computers,

or even downhole data transmission devices.   In some cases,

data could be provided from proppant hoppers, fracturing

fluid tanks, mixing equipment, and the like, to be used in

the process.   A local storage device may receive the output

5   of the inventive method, or it may be displayed on a

monitor.   Additionally, output may be comprised of a visual

or graphical display, and may be sent to a printer, plotter,

or storage device as needed.

10   **FURTHER DETAILED DESCRIPTION**

The numerical algorithm employed in this invention

comprises an efficient technique to determine the local

width of a hydraulic fracture due to local pressure applied

to the fracture faces by the injection of hydraulic fluid

15   and proppant into the fracture.   Further, a method to track

the dimensions and width of said fracture as it grows as a

function of time is shown.   The hydraulic fracture(s) may

span any number of layers in a laminated reservoir, with the

restriction that all layers must be parallel to each other,

20   as depicted for example in Figure **12**.   Layers may be

inclined at any angle to the horizontal.

Figure **12** shows a section through multiple hydraulic

fractures in a layered reservoir. The calculation of the

fracture width due to the pressure from the injected fluids

and proppant mixture is determined by taking into account,

5   accurately and efficiently, the physical properties of each

layer comprising the laminated reservoir. The technique

used to calculate the relationship between the layered

reservoir and the growing hydraulic fracture is based on a

well-established numerical technique called the Displacement

10   Discontinuity Boundary Element Method (hereafter "DD"). The

method is extended to enable efficient and accurate

calculation of the physical effects of layering in the

reservoir by the use of a Fourier Transform Method, whereby

the relations between stress and strain in the layered

15   reservoir are determined. The numerical method assumes that

each hydraulic fracture is divided into a regular mesh of

rectangular elements, as depicted in Figure **13**, wherein each

numerical element contains its own unique properties.   Such

properties include applied fluid and proppant pressure,

20   fluid and proppant propagation direction and velocity, local

reservoir properties, stress-strain relations, and fracture

width.

18

Figure **13** shows a numerical mesh of elements subdividing

the fracture surface for purposes of calculation. In cases

where the numerical element coincides with the fracture edge

or tip (see Figure **14**), certain additional information is

5   uniquely defined to such elements. For example, such

information may include the local velocity of propagation of

the fracture tip, the special relationship between the fluid

in the fracture and the surrounding layered reservoir, and

how the fluid and reservoir physically interact with each

10   other. This interaction is accounted for by means of

special properties assigned to the tip elements, comprising

the interaction between a fluid-filled fracture and the host

material it is fracturing.

Figure **14** reveals a fracture outline on a numerical mesh.

15   Each numerical element depicted in Figure **13** or **14** relates

to every other element in the numerical mesh by means of

special mathematical relationships. We refer to elements

as: (1) sending or source elements, and (2) receiver

elements. A source element sends a signal representing a

20   mathematical relationship to a receiver element. The signal

in our case is the applied fluid pressure in that portion of

the fracture. The receiver signal comprises the stress and

strain experienced at the receiver location due to the

applied pressure at the source element location. Many of

these signals between source and receiver element are

duplicated in the numerical mesh, and in these cases,

5   special algorithms are designed to dramatically minimize the

volume of storage required, so that only unique signals

between different elements need to be stored.

The signals between each unique pair of receiver and

source elements are stored in the computer memory or on

10   physical storage device in a matrix. The hydraulic fracture

propagation numerical method is designed so that the

fracture propagates in a finite number of time steps. At

each time step, the signal matrix is invoked, extracting

those signals which are active over the part of the

15   numerical mesh that is covered by the current configuration

of the hydraulic fracture. This matrix is then used to

build a system of numerical equations that are solved for

the fracture width at the current time -- at each active

element location.

20   The solution of the equation system is accomplished using

an extremely efficient numerical iterative solution

technique, referred to as the L1D Iterative Equation Solver.

Incorporated by reference herein is reference 15, which discloses the L1D Iterative Equation Solver. This solver has been specifically designed to solve this type of equation system in a very efficient and accurate manner.

5   During each fracture propagation step, another matrix of signals is constructed, the matrix comprising the physical behavior of the fluid in the hydraulic fracture, which relates the local fluid pressure to the local fracture width. This system of equations is also solved iteratively

10   for local fluid pressures at each time step.

The combined system of equations must be coupled together in an efficient manner, so that they feed off each other until a balanced solution of fluid pressure and fracture width is obtained at each time step. This coupling between

15   the two equation systems is accomplished by means of a special numerical algorithm that efficiently and accurately ensures that the correct solution is obtained. The entire system is designed to ensure that no fluid or proppant is unaccounted for in any time step.

20   The above process is repeated at each time step, thereby allowing the calculation of the way in which the fracture grows as a function of time. At each time step, the

algorithm predicts which elements are active (i.e., filled

with fluid and proppant), and the fracture width and

fracture pressure on each active element. A complete

description of the process of the propagation of a hydraulic

5   fracture is thus obtained.

Solutions of the multi-layer equilibrium equations are

provided. A three-dimensional body is assumed. The theory

also applies to the two-dimensional cases (plane strain,

plane stress, antiplane strain). The method provides an

10 efficient way of determining the solution to the equilibrium

equations:

$$\sigma_{ij,j} + b_i = 0 \tag{1}$$

15 for a transversely isotropic elastic medium with a stress

strain relationship given by:

$$\sigma_{ij} = C_{ijkl}\varepsilon_{kl} \tag{2}$$

20   In the case of a transversely isotropic three-

dimensional elastic medium, there are five independent

22

material constants.   The strain components in (2) are given

by

$$\varepsilon_{kl} = \frac{1}{2}\left(u_{k,l} + u_{l,k}\right) \tag{3}$$

5

For a medium comprising multiple parallel layers each

of which is homogeneous (see Figure **15**), it is possible to

obtain a solution to the governing equations (1)-(3) by

means of the Fourier Transform.   Figure **15** represents a

10   schematic showing multiple parallel layers in three-

dimensional case.

By substituting (3) and (2) into (1) and by taking the two-

dimensional Fourier Transform with respect to x and y:

15   $$\hat{u}_j(m,n,\bar{z}) = \int\limits_{-\infty}^{\infty} \int\limits_{-\infty}^{\infty} e^{i(mx+ny)} u_j(x,y,z)\,dx\,dy \tag{4}$$

of the resulting equilibrium equations in terms of the

displacements, we obtain a system of ordinary differential

equations in the independent variable z. This system of

20   ordinary differential equations determines the Fourier

Transforms of displacement components u_x, u_y, and u_z:

23

$$L\left(C_{ijkl}\right)\begin{bmatrix}\hat{u}_x \\ \hat{u}_y \\ \hat{u}_z\end{bmatrix} = \begin{bmatrix}\hat{b}_x \\ \hat{b}_y \\ \hat{b}_z\end{bmatrix} \tag{5}$$

5   For a layered material, there is a system of differential equations of the form (5) for each layer, each of whose coefficients are determined by the material properties of the layer. It is possible to solve the system of differential equations for a typical layer l to obtain the general solution to the r th displacement components in

10   the form:

$$\hat{u}_r^l = \sum_j d_{jr}^l e^{\alpha_j kz} A_j^l(k) \tag{6}$$

where $k = \sqrt{m^2 + n^2}$

15   In the case of repeated roots of the characteristic equation associated with (5), which occurs for the important case of isotropic layers, the system (5) has the general solution:

$$\hat{u}_r^l = \sum_j \left(d_{jr}^l + f_{jr}^l z \right) e^{\alpha_j kz} A_j^l(k) \tag{7}$$

Here d_{jr}^l and f_{jr}^l are constants that depend on the

material constants of the layer, the α_j are the roots of

5   the characteristic equation for the system of ordinary

differential equations, and the $A_j^l(k)$ are free parameters of

the solution that are determined by the forcing terms b_j in

(1) and the interface conditions prescribed at the boundary

between each of the layers (e.g. bonded, frictionless,

10 etc.).

Substituting these displacement components into the

stress strain law (2), we can obtain the corresponding

stress components: $\hat{\sigma}_{xx}$, $\hat{\sigma}_{yy}$, $\hat{\sigma}_{zz}$, $\hat{\sigma}_{xy}$, $\hat{\sigma}_{xz}$, and $\hat{\sigma}_{yz}$, which can

be expressed in the form:

15

$$\hat{\sigma}_{pq}^l = \sum_j \left(s_{jpq}^l \right) e^{\alpha_j kz} A_j^l(k) \tag{8}$$

In the case of repeated roots the stress components

assume the form:

$$\hat{\sigma}^l_{pq} = \sum_j \left(s^l_{jpq} + t^l_{jpq} kz \right) e^{\alpha_j kz} A^l_j(k) \tag{9}$$

For each layer and for each sending DD element located at a particular z coordinate, there are a set of six parameters $A^l_j(k)$ that need to be determined from a system of algebraic

5   equations that express the required body forces and boundary conditions in the model. Once the $A^l_j(k)$ have been determined, it is possible to calculate the influences of any DD having the same z component on any receiving point in any layer by taking the inverse Fourier Transform:

10

$$u_j = \frac{1}{(2\pi)^2} \int_{-\infty}^{\infty} \int_{-\infty}^{\infty} e^{-i(mx+ny)} \hat{u}_j \, dm \, dn \tag{10}$$

of (6)-(9).

15   One of the major computational problems in the procedure outlined above is the inversion process represented by (10), which involves the numerical inversion of a two-dimensional Fourier Transform for each sending-receiving pair of DD elements. The method we propose uses

an exponential approximation of the spectral solution

coefficients $A_j^l(k)$ of the form:

$$A_j^l(k) - A_j^l(\infty) \approx \sum_j a_{jr}^l e^{b_{jr}^l k} \qquad (11)$$

5

Here $A_j^l(\infty)$ represents the high frequency components of

the spectrum of the solution, which represents the singular

part of the solution in real space.

The inversion process can be achieved by evaluating

10 integrals of the form:

$$I_j^{pl} = \frac{1}{(2\pi)^2} \int\limits_{-\infty}^{\infty} \int\limits_{-\infty}^{\infty} \left[A_j^l(k) - A_j^l(\infty) \right] k^p e^{\alpha_j^l kz} e^{-i(mx+ny)} dmdn$$

or

15 $$I_j^{pl} \approx \frac{1}{(2\pi)^2} \sum_j a_{jr}^l \int\limits_{-\infty}^{\infty} \int\limits_{-\infty}^{\infty} k^p e^{k(\alpha_j^l z + b_{jr}^l)} e^{-i(mx+ny)} dmdn \qquad (12)$$

which can be evaluated in a closed form. The shifted

components $\alpha_j^l z - b_{jr}^l$ in (12) represent a finite number of

complex images that approximate what would be an L-fold

27

infinite Fourier Series (for L layers) that would be required to represent the Green's function in a closed form using the method of images. Typically three or four complex images suffice to give a high order of accuracy.

5   The expressions of the form (12) are not much more complicated than the pair-wise DD influences that apply for a homogeneous elastic medium. One difference in this case is that for each sending DD element, the expansion coefficients a'_{jr} and b'_{jr} for each layer need to be determined

10   by solving the appropriate set of algebraic equations and performing the exponential fit (11) of these coefficients. Once these coefficients have been determined we have a very efficient procedure to determine the influences between DD elements.

15   For a regular array of DD elements there is an additional saving that can be exploited. In this case only the influence of a single sending DD element at each horizon (i.e., z level) needs to be determined in order to determine the whole influence matrix. For example, the source DD

20   elements in layer 1 denoted by the cross-hatched, hatched, and unshaded circles each have the same set of layer 2

exponential expansion coefficients a_{jr}^l and b_{jr}^l. (see Figure 16). Below is a description of how to construct arbitrarily oriented DD influence coefficients.

5   A DD influence at a specified point *within* a given layer is constructed by constructing a pseudo interface parallel to the layering across which there can be a jump in the displacement field. To construct a normal DD a jump in u_z is specified, whereas to construct a shear or ride DD a jump in u_x or u_y is specified. This technique limits the

10   orientation of DD components to be aligned with the pseudo interface that is parallel to the layering.

It is, however, desirable to have DD components that specify jumps in the displacement field which are across interfaces that are not parallel to the layering in the

15   material. In particular, for hydraulic fracturing problems in the petroleum industry, it is important to be able to model vertical fracture planes that are perpendicular to the horizontally layered material. In this case, and for arbitrarily oriented DDs, it is possible to construct a DD

20   field of a desired orientation, by utilizing the duality relationship between the stresses due to a force discontinuity (or point force) and the displacements due to

29

a displacement discontinuity. The solution to a force

discontinuity in the r th direction can be constructed by

taking $b_r = \delta(x, y, z)F_r$, where $\delta(x, y, z)$ represents the

Dirac delta function.

5   Having obtained the stresses due to a force

discontinuity:

$$\hat{\sigma}_{ij} = \hat{\gamma}_{ijr}F_r \qquad\qquad (13)$$

10   it is possible to determine the displacements due to a DD

according to the following duality relation:

$$\hat{u}_r = \hat{\gamma}_{ijr}D_{ij} \qquad\qquad (14)$$

15   One key component is to construct a planar Green's

function or influence matrix, which represents the

influences of all the DDs that lie in a vertical fracture

plane. The influence matrix will only represent the mutual

influences on one another of DDs that lie in the fracture

20   plane. However, it will implicitly contain the information

about the variations in material properties due to the

layering. Figure **17** depicts the basic algorithm.

A reduced influence matrix can be constructed by any

numerical method, including that proposed above, which can

5   represent rigorously the changes in material properties

between the layers. For example, the finite element method

or a boundary integral method in which elements are placed

on the interfaces between material layers. The in-plane

influence coefficients would be calculated by means of the

10   following procedure.

To calculate the influence of the ij th in-plane DD on

the kl th DD anywhere else on the fracture plane, the value

of the ij th DD would be assigned a value of unity and all

the other fracture plane DDs would be set equal to zero.

15   The boundary integral or finite element solution on the

interfaces between the material layers would then be

determined so as to ensure that there is compatibility in

the displacements between the material layers as well as a

balance in the forces between the layers at the interface.

20   Once numerical solution has been calculated for the whole

problem, the corresponding stresses on each of the in-plane

DD elements can be evaluated to determine the in-plane

31

stress influence of that unit DD on all the other DDs in the

fracture plane. By repeating this process for each of the

DDs that lie in the fracture plane, it is possible to

determine the in-plane influence representing the effect

5   that each DD in the plane has on any of the other in-plane

DDs. By allowing the interface solution values to react to

the sending DD element, the effect of the layers has been

incorporated implicitly into this abbreviated set of

influence coefficients.

10   The numerical procedure outlined to construct the

desired in-plane influence matrix would take a considerable

amount of time to compute. Indeed, such a process would

likely exclude the possibility of real time processing, but

could conceivably be performed in a batch mode prior to the

15   desired simulation being performed. The semi-analytic

method outlined above would be much more efficient, as the

fully three-dimensional (or two-dimensional, in the case of

plane strain or plane stress), problem that needs to be

solved to calculate the influence of each DD element has

20   been effectively reduced to a one-dimensional one.

Numerical models for multi-layered materials require

that the interface between each material type is numerically

"stitched" together by means of elements. For example, a

boundary element method implementation would require that

each interface between different material types is

discretized into elements. A finite element or finite

5   difference method implementation would require that the

entire domain is discretized into elements. In the current

patent, the material interfaces are indirectly taken into

account without the requirement of explicitly including

elements away from the surface of the crack or fracture.

10   The implication thereof, is a dramatic reduction in the

number of equations to be solved, with a commensurate

dramatic decrease in computer processing time. In addition,

accuracy of the solution is maintained. One aspect of this

invention which distinguishes it from previous work is that

15   it is capable of solving problems in multi-layered elastic

materials with arbitrarily inclined multiple cracks or

fractures in two or three-dimensional space.

Another aspect of this invention which distinguishes it

from prior art is that elements can intersect layers. This

20   is accomplished by taking special care of the mathematical

stress/strain relationships across interfaces in such a way

as to obtain the correct physical response for the element

which is located across the interface(s).

Figure **17** shows a flowchart of the present invention in

which input layer dimensions and physical properties are

5   provided.   Then, the fracture plane is divided into

elements, and for each horizontal row of elements, the

'calculations are performed.   Further, one may assemble the

matrix of in-plane DD influences and then solve the

equations to determine an estimate of the crack opening.

10   References **1-3** below are classic papers that establish

the Fourier scheme to solve elastic multi-layer problems,

but do not utilize the inversion scheme proposed here.   In

references 1 and 2, a propagator matrix approach is

suggested to solve the system of algebraic equations

15   necessary for the Fourier scheme, but this particular

scheme will become unstable for problems with many layers.

References 4 and 5 use exponential approximation for

inversion.   The methods in those references do not give rise

to the complex images generated by the algorithm presented

20   in this invention that so efficiently represent the effect

of many layers.   Reference 5 extends the propagator approach

used in references 1 and 2 to solve the algebraic equations

of the Fourier method. Reference 5 discloses an inversion

scheme that is an integral part of the propagator method.

This method involves an exponential approximation, similar

to that proposed in this patent, but it is applied to only

5   one part of the propagator equations. As a result, a least

squares fit of many terms (more than 50) is required to

yield reasonable results using the teachings of this

reference. Apart from stability issues involved with

exponential fitting, the large number of terms would

10   probably be less efficient than using direct numerical

integration for inversion. The exponential fit of the

spectral coefficients that we propose involves less than

five terms.

   References 6 through 10 extend the Fourier method to

15   transversely isotropic media. References 7-10 use the

propagator matrix for solving the algebraic equations, while

reference 6 below proposes direct solution. All these

methods of solution would be numerically unstable for

problems with many thick layers. While reference 10

20   proposes numerical inversion using continued fractions,

little mention is made of the inversion process.

References 11 and 12 describe methodologies for multi-layer dielectric materials containing point electrical charges, or line charge distributions aligned parallel to interfaces (i.e., with different Green's functions to those

5 used in elasticity).

Reference 13 describes a so-called "sweeping" algorithm to solve layered systems. The method disclosed in reference 13 is essentially the classic block LU decomposition for a block tri-diagonal system. In this invention, we use this

10 algorithm to obtain a stable solution of the algebraic equations that determine the Fourier spectral coefficients in each of the layers. This method is particularly effective for problems in which the layers are thick or the wave-numbers are large.

15 It is recognized that other mathematical relationships may be used in the invention to achieve the same commercial or physical purpose. While not employing exactly the same equations, such methods are within the scope of the invention as set forth herein.

20 In Figure **18**, a sample FracCADE zone screen is shown whereby an operator of the software can choose the formation laminations that apply to the wellbore under examination in

carrying out the inventive method.   Figure **19** shows the

FracCADE fracturing fluids screen having a fluids rheology

table with physical parameters necessary to carry out the

inventive method.   Figure **20** shows a sample output (as on a

5   computer monitor or printed) which includes stress, fracture

width, and proppant distribution.   The fracture profile and

proppant concentration levels achieved in each portion of

the fracture are shown.   Further, the fracture width is

provided for designing and evaluating fracture growth.

10   The following references are hereby incorporated by

reference as if set forth here in their entirety:

1. Ben-Menahem, A. and Singh, S.J. 1968. *Multipolar elastic*

fields in a layered half space. Bull. Seism. Soc. Am.

58(5). 1,519-72.

15 2. Singh, S.J. 1970. *Static deformation of a multi-layered*

half-space by internal sources. J. Geophys. Res. 75(17).

3,257-63.

3. Chen, W.T. 1971. *Computation of stresses and*

displacements in a layered elastic medium. Int. J. Engng

20   Sci. vol. 9. 775-800.

4. Sato, R. and Matsu'ura, M. 1973. *Static deformations due*

to the fault spreading over several layers in a multi-

layered medium *Part I: Displacement*. J. Phys. Earth. 21.

227-249.

5. Jovanovich, D.B., Husseini, M.I. and Chinnery, M.A.

1974. *Elastic dislocations in a layered half-space - I.*

5   *Basic theory and numerical methods*. Geophys. J. R. astro.

Soc. 39. 205-217.

6. Wardle, L.J. 1980. *Stress analysis of multilayered*

anisotropic elastic systems subject to rectangular loads.

CSIRO Aust. Div. Appl. Geomech. Tech. paper no. 33. 1-37.

10   7. Singh, S.J. 1986. *Static deformation of a transversely*

isotropic multilayered half-space by surface loads.

Physics of the Earth and Planetary Interiors. 42. 263-

273.

8. Pan, E. 1989. *Static response of a transversely*

15   *isotropic and layered half-space to general surface*

loads. Physics of the Earth and Planetary Interiors. 54.

353-363.

9. Pan, E. 1989. *Static response of a transversely*

isotropic and layered half-space to general dislocation

20   *sources. Physics of the Earth and Planetary Interiors.*

58. 103-117.

10.   Pan, E. 1997. *Static Green's functions in multilayered half spaces*. Appl. Math. Modelling. 21. 509-521.

11.   Chow, Y.L., Yang, J.J. and Howard, G.E. 1991. *Complex images for electrostatic field computation in multilayered media*. IEEE Trans. on Microwave Theory and Techniques. vol. 39. no. 7. 1120-25.

12.   Crampagne, R., Ahmadpanah, M. and Guiraud, J.-L. 1978. *A simple method for determining the Green's function for a class of MIC lines having multilayered dielectric structures. IEEE Trans. on Microwave Theory and Techniques*. vol. MTT-26. No. 2. 82-87.

13.   Linkov, A.M., Linkova, A.A. and Savitski, A.A. 1994. *An effective method for multi-layered media with cracks and cavities*. Int. J. of Damage Mech. 3. 338-35.

14.   Ryder, J.A. and Napier, J.A.L. 1985.   *Error Analysis and Design of a Large Scale Tabular Mining Stress Analyzer*.   Proc: Fifth Int. Conf. On Num. Meth. In Geomech. Nagoya.   1549-1555.

15.   J.A. Ryder, Cairns, E.G. Beer, J.R. Booker, and J.P. Carter,   *Optimal Iteration Schemes Suitable for General Non-linear Boundary Element Modelling Applications*: Proceedings of the 7th International Conference on

Computer Methods and Advances in Geomechanics, Balkema
Rotterdam, 1991.

Other embodiments of this invention beyond the exact

5   specification of the examples set forth herein have been

suggested and still others may occur to those skilled in the

art upon a reading and understanding of the this

specification. It is intended that all such embodiments be

included within the scope of this invention.